
PUFFIN GLASS BEAD

Reflective glass bead potter for road marking paint. Very suitable for Thermoplast paint.

1. Properties

COLOR	Clear
SIEVE NO 20(0.85MM)	100 %
DENSITY (g/cm ³)	2.5

2. Characteristics

Clear sparkle glass powder

3. Usage

Road marking pain

1) Application

Dropping glass beads in to the paint film immediately after applied. Use the suitable size gradation and type of glass beads, depending on the requirements of the road marking. Glass beads must be 50 to 60% paint embedded to secure durability and night visibility. This product has a 30% premix glass beads content

The temperature of the substrate must be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying

4. Precaution

1) Ensure to clean the surface before application.

2) Health and safety : Please observe the precautionary notices displayed on the container.

Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

3) Storage : The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care. Shelf life at 23 °C : 12Month(s)

5. Packing :

4 & 25 Kg