

Jl. Pangeran Jayakarta 121/3-4, Jakarta Pusat www.puffinpaint.com Telp: 021-62313238

## **PUFFIN THINNER EPOXY**

Suitable for Puffin Epoxy paint thinner. This product also can be use as cleaner for pumps and tools before and after painting.

## 1. Properties

<b>Property Description</b>	TestStandard	RESULT
Solids by volume	ISO 3233	0%
Flash point	ISO 3679 Method 1	12 °C
Density kg/l	Calculated	8.0
VOC-US/Hong Kong	US EPA method 24 (tested) (CARB(SCM)2007, SCAQMD rule 1113, Hong Kong	780 g/l
VOC-EU	IED (2010/75/EU) (theoretical)	780 g/l
VOC-China	GB/T 23985-2009 (tested)	792 g/l

The provided data is typical for factory produced products, subject to slight variation depending on colour.

2.	<u>Storage</u>	The product must be stored in accordance
----	----------------	--

with national regulations. Keep the

containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed.

Handle with care.

Shelf life at 23 °C / 48 month(s)

## 3. Caution This product is for professional use only. The

applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to puffin's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This

guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible puffin representative for approval before commencing the work

4. Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

5. Colour variation

Colour and gloss retention on topcoats/finish coats may vary depending on type of colour, exposure environment such as temperature, UV intensity etc., application quality and generic type of paint. Contact Puffin Customer Service for further information.

6. Disclaimer

The information in this document is given to the best of Puffin's knowledge, based on laboratory testing and practical experience. Puffin's products are considered as semifinished goods and as such, products are often used under conditions beyond Puffin's control. Puffin cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Puffin reserves the right to change the given data without further notice.

Users should always consult Puffin for specific guidance on the general suitability of this product for their needs and specific application practices.

7. Packaging

1 & 5 & 20 L